

baseLine

WASHING AND DRYING



Swissmade 



SCHULTHESS

Washing and drying

Swissmade 

A compact professional machine for small commercial use.
The new baseLine machines make laundry care easy – efficient, fast and user-friendly!

With the baseLine series, Schulthess has developed a range of machines that are tailored to the needs of small businesses and service providers. baseLine machines are multi-lingual, robust and powerful, and are used where home appliances reach their limits. The first-class quality and long service life as well as simple operation guarantee a smooth operation.

Customised programmes

In addition to the tried-and-tested washing programmes with practical programme options (prewash, intensive, express wash, energy saving, spinning, etc.), Schulthess has expanded its range of segment-specific programmes. The 35 additional profiClean programmes are designed to meet the needs of particular branches of industry, such as schools, childcare centres, hairdressers, doctors' surgeries, cosmetic studios and commercial cleaners (e.g. mop care) or small businesses.

35 «profiClean»-programmes

Commercial operations (13):

Including 30 °C capes, 40 °C Express for terry towels, 60 °C working clothes, 90 °C kitchen towels intensive

Building cleaners (13):

Including 60 °C mop (with pre-rinse), 40–85 °C mop disinfection, 60 °C wipes, 70 °C autoClean

Wellness Centre (9):

Including 40 °C Express for terry towels, 60 °C cotton disinfection, 60 °C duvet, pillows

Plinth with fluff filter drawer



Heavily soiled mop pads and wipes are efficiently cleaned with the profiClean programmes for building cleaners. In order to prevent the fluff from clogging the drainpipes, the baseLine

washing machine plinth comes with an integrated lint trap drawer that is specifically developed to meet the needs of building cleaners.

The optimal height of 40 cm of the chrome steel plinth also offers an ergonomic advantage when loading and unloading the washing machine and guarantees smooth water discharge at the wall outlet.

baseLine TC 7730 dryer

The baseLine TC 7730 condensation dryer with its electronically controlled drying programmes is the ideal complement to the washing machine:

Cotton Mangle Moist, Iron Damp, Slightly Dry, Cabinet Dry, Extra Dry, and additional programmes such as Mixed Laundry, Synthetic Laundry, Fine Laundry and Shirts.

Optionally selectable depending on the programme: Dry+, Express, Antibac and time preset.

Innovations

The new baseLine machine generation impresses with its 34 profiClean programmes that are exactly tailored to your needs; it also provides 24 free programme slots. The machines newly feature a modern interactive 4.3" colour display with profiClean programme selection button and a new, simple programming software.



TOP STANDARD

Schulthess baseLine 7720



Load capacity: 1 – 7 kg
Spin speed: 1500 – 200 rpm

Equipment

- Large 4.3" colour display
- Drum vanes for 3D-Washing
- LED drum lighting
- Drum capacity: 60 l
- Spin speed: 1500 rpm
- g Factor 605
- Residual moisture 44%
- With drain valve or drain pump
- Language selection button (23 languages)
- profiClean programme button
- Favorites for your 6 favourite programmes
- Programme progress and remaining time display
- Door opening angle 180°
- Door hinge right or left

Programmes

- 35 profiClean programmes for small commercial businesses, building cleaners and special programmes
- 24 freely programmable slots
- 40–85°C disinfection programmes
- **Programme groups** Sportswear, Businesswear, Homecare, Antibac

Safety systems

- Control display for water intake / drainage
- Imbalance sensor / child lock / foam level monitoring

Options

- Hot water connection
- Programme expansion module with PC interface
- Coin box interface
- Machine plinth in chrome steel, H: 35.5 cm
- Machine plinth with fluff filter drawer, H: 40 cm

TOP STANDARD

Schulthess baseLine TC 7730



Load capacity: 1 – 7 kg

Equipment

- Condensation dryer
- Large 4.3" colour display
- Stainless steel drum
- LED drum lighting
- Drum capacity: 118 l
- Electronically and time-controlled drying programmes
- Residual moisture measurement
- Language selection button
- Excellent noise insulation
- Crease protection
- Programme progress and remaining time display
- Door opening angle 180°
- Door hinge right or left

Programmes

- Automatic programs with 5 drying levels from mangle moist to extra-dry.
- Time-controlled drying programmes 10 – 150 minutes
- Gentle drying at reduced temperature
- 7 kg of laundry is cabinet dry in 83 min. (cotton, 1600 rpm)

Safety systems

- Temperature monitoring
- Child lock / condensed water drainage monitoring

Options

- Stacking kit for washer-dryer tower
- Coin box interface
- Machine plinth in chrome steel, H: 35.5 cm

Company or brand name	Schulthess
Type of appliance	Washing machine
Type or sales description	baseLine 7720
Product number	
Model with drain pump (P)	7720.1PU
Model with drain valve (V)	7720.1UV

Application features

Load capacity	max. kg	7
Drum capacity	l	60
Spinning speed	max. rpm	1500
g Factor	g	605
Residual moisture ¹⁾	%	44

Structural design

Footed appliance with work surface	•
Door hinge ³⁾	r/l/w

Dimensions

Height	cm	85
Width	cm	60
Depth including distance from wall	cm	67
Depth with door open (front loader)	cm	110
Height (adjustable)	cm	1
Weight when empty	kg	90

Equipment

Detergent tank and drum	chrome-nickel steel
Loading opening	Ø cm 34 / 180°
Programme time display	•
Load quantity display	•
Automatic door opening	•
LED drum lighting	•
Connecting cable	m 1.6
Drain:	
– Drain hose with benda, only model (P)	m 1.5
– Model with drain pump (P)	Ø mm 21
– Model with drain valve (V)	Ø mm 50

Electric power and water supply

Electrical connection	400V 2N~ / 50Hz / 4,6kW / 10A
Voltage / connected loads / fuse	230V 1N~ / 50Hz / 2,3kW / 10A
Water connection	
– Pressure hose G ¾" with fine filter	m 1,5
– Can be connected to cold water / hot water	cold water / hot water 70 °C
– Water pressure	bar 1–10

Options

– Door hinge left	
– Hot water connection	
– Drain valve or drain pump	
– Connection for 8 liquid detergents with dosing pump	
– Machine plinth	
– Machine plinth with drawer for fluff filter	

Safety and service

Conforms to the European Machinery Directive	2006/42/EC
Country of origin	Switzerland
Guarantee	1 year
Service by	Schulthess Maschinen AG
Name and address of supplier	Schulthess Maschinen AG, CH-8633 Wolfhausen/ZH

Explanations:

- Available or yes • Not available or no
- 1) Values determined in the 60°C cotton programme.
- 3) Door hinge: l = left, r = right, w = can be changed
Example: l/w means that the machine is delivered with the door hinge to the left, but the direction of opening can be changed.
- 7) Information on switchover options can be found in the installation instructions, where required.

Company or brand name	Schulthess
Type of appliance	Condensation dryer
Type or sales description	baseLine TC 7730
Product number	7730.1U
Load capacity	max. kg 7

Structural form

Footed appliance with work surface	•
Standard unit for wash and dry column	•
Door hinge ³⁾	r/l/w

Dimensions⁴⁾

Height	cm	85
Width	cm	60
Depth including space from wall	cm	64
Height for built-in installation	cm	85,5
Depth with door open	cm	122
Height adjustable	cm	2

Drying control

By time selection ⁵⁾	•
Automatic by electronic moisture detection ⁶⁾	•

System and equipment

Drying technology	Air condensation system
Programme time display	•
Load quantity display	•
Automatic door opening	•
Loading opening	cm vorne, Ø 36 / 31 / 180°
LED drum lighting	•
Connecting cable	m 1,5
Outlet hose	m 2 / Ø 22 mm
Condensate drainage in container / Drainage direct	•
Exhaust line	–
Maximum drainage height	m 1
Exhaust hose Ø 100 mm	m –

Power supply

Electrical connection ⁷⁾	
Voltage	V 400V 2N~ / 230V 1N~
Connected values	kW 2,8 / 2,1
Fuse protection	AT 10 / 10

Safety and service

Conforms to the European Machinery Directive	2006/42/EC
Country of origin	Switzerland
Guarantee	1 year
Service by	Schulthess Maschinen AG
Name and address of supplier	Schulthess Maschinen AG, CH-8633 Wolfhausen/ZH

Explanations:

- Available or yes • Not available or no
- 3) Door hinge: l = left, r = right, w = can be changed
Example: l/w means that the machine is delivered with the door hinge to the left, but the direction of opening can be changed.
- 4) The stated dimensions are minimum dimensions for the niche where the machine is built in. Further dimensions can be found in the dimension sheets.
- 5) Set the degree of drying according to the laundry items, as shown in the operating instructions.
- 6) Degree of drying is maintained automatically.
- 7) Information on switchover options can be found in the installation instructions, where required.

Note: State of the table details as december 2017, subject to further developments.

Schulthess Maschinen AG

Landstrasse 37, CH-8633 Wolfhausen ZH

Tel. +41 55 253 51 11

international-sales@schulthess.ch

www.schulthess.ch

