



2 ZONES INDUCTION BOILING TOP

316025 - PIN4E9

SPECIFICATIONS

Tecno90 by Tecnoinoxis a modular range designed for intense use.

Tecno90 is ideal for kitchens in hotels and large restaurants, as well as catering facilities. It satisfies all requirements in terms of reliability, power and production capacity, capable of serving a large number of diners

offering the highest quality results.

Tecno90 in particular is made using high quality and depth materials to ensure the products are robust and resistant to corrosion. The Tecno90 line is designed to be easy to clean and offer excellent levels of hygiene.

With its wide range of appliance and composition flexibility, Tecno90 satisfies the requests of even the most demanding chefs.

ROBUST AND LONG-LASTING

Tops in 2 mm AISI 304 Stainless steel.

SAFETY

The gas appliances are certified by German body DVGW and have passed the most stringent safety tests. The electrical appliances are tested at our facility and are CE certified.

FINISHES

Tecno90 has a strong design focus both on aesthetics and functionality. The broad, robust handles have good grip and are easy to clean. They also protect the doors against knocks from trolleys. The single-piece side panels complete the island, unifying it and providing solidity. They also come in a coated version like

SEALS

Made from steel mesh and glass fibre, they seal the door and can withstand high temperatures for many years.

POWERFUL UNIFORM COOKING

Chefs can count on substantial power and excellent performance in terms of cooking uniformity. ULTRA-RELIABLE

CETTA RELIABLE

above 99%.

TECHNICAL COMPARTMENT

The majority of the units are fitted with a technical compartment at the back for connections and hookups.

APPLIANCES THAT FIT TOGETHER PERFECTLY AND ARE EASY TO INSTALL

The exclusive Tecnoinox fastening system makes the appliance easy to install and fit together. The feet are easy to adjust and made from AISI 304 stainless steel.

EASY TO CLEAN

The moulded tops and tanks with rounded corners, wide grooves and anti-spill edges mean infiltrations are reduced to a minimum and the products are easy to clean. The vents can be removed for cleaning and the units fit together perfectly, which helps to ensure a good level of hygiene is maintained.

COOKERS AND INDUCTION COOK TOPS

- Glass ceramic top, 6 mm thick.
- The heating zones allow you to choose to switch on the smaller circuit or both circuits, depending on the pan size.
- Ultra-rapid tungsten resistors.
- Easy to clean.

TECHNICAL DATA

Total Power	10 kW	Width	40 cm
EL Power	10 kW	Depth	90 cm
Frequency	50/60 Hz	Height	28 cm
Voltage	400 3 ~ V	Packaging Width	100,0 cm
Cooking Zones Power	2x5 n°- kW	Packaging Depth	46,0 cm
Number of Cooking zones	2 n°	Packaging Height	58,0 cm
Foot high	15 mm	Net Weight	35,0000 kg
Foot adjustment	15/25 mm	Gross Weight	43,0000 kg
IPX	4	Volume	0,2600 m ³

ACCESSORIES

- 399516: WATER TAP WITH SWIVEL ARM
- 399569: WATER TAP WITH SWIVEL ARM FOR RANGES WITH CHIMNEY
- 399573: CLOSING ELEMENTS (2 PCS) FOR BASES AND TOPS L=90CM